



FROM RESIDENTIAL TO COMMERCIAL WASTE-DISPOSAL, IT'S INDIA'S TRU-CHOICE.

Long lasting
SWR Piping Systems.



Pipes as per
IS:13592



Fittings as per
IS:14735



PRODUCT RANGE

Pipes : 40mm - 160mm

Fittings : 75mm - 160mm

EXTENSIVELY USED IN



HOSPITALS



RESIDENTIAL



HOTELS

Type A



VENTILATION
PIPE WORK



RAIN WATER
DISCHARGE &
HARVESTING

Type B



SOIL AND WASTE
DISCHARGE SYSTEM

SWR FITTINGS WITH RUBBER RING JOINT

COUPLER



75mm to 160mm

BEND 87.5 °



75mm to 160mm

BEND WITH DOOR



75mm to 160mm

SINGLE TEE



75mm to 160mm

SINGLE TEE
WITH DOOR



75mm to 160mm

SINGLE Y



75mm to 160mm

SINGLE Y WITH DOOR



75mm to 160mm

DOUBLE Y



75mm & 110mm

DOUBLE Y WITH DOOR



75mm & 110mm

BEND 45°



75mm to 160mm

CLEANSING PIPE



75mm to 160mm

REDUCER



110mmx75mm &
160mmx110mm

REDUCING TEE



160mm X 110mm

REDUCING TEE
WITH DOOR



160mm X 110mm

SWR FITTINGS WITH SOLVENT JOINT

COUPLER



75mm & 110mm

BEND 87.5 °



75mm to 160mm

BEND WITH DOOR



75mm to 160mm

SINGLE TEE



75mm to 160mm

SINGLE TEE WITH DOOR



75mm to 160mm

SINGLE Y



75mm to 160mm

DOUBLE TEE



75mm & 110mm

DOUBLE TEE WITH DOOR



75mm & 110mm

SINGLE Y WITH DOOR



75mm to 160mm

DOUBLE Y



75mm & 160mm

DOUBLE Y WITH DOOR



75mm & 110mm

CLEANSING PIPE



75mm to 160mm

REDUCER



160mm x 110mm

BEND 45 °



75mm to 160mm

VENT COWL



75mm & 110mm

PIPE CLIP*



75mm to 160mm

REDUCING TEE



160mm x 110mm

REDUCING TEE WITH DOOR



160mm x 110mm

NAHANI TRAP WITH JALI



110mm x 75mm

NAHANI TRAP WITHOUT JALI



110mm x 75mm

MULTI FLOOR TRAP (WITH JALI) 4" HT



110mm x 75mm

MULTI FLOOR TRAP (WITHOUT JALI) 4" HT



110mm x 75mm

ACCESS / SOCKET PLUG*



50mm to 110mm

P TRAP



110mm x 110mm & 125mm x 110mm

ROUND JALI



110mm x 110mm

APPLICATIONS

- Inside & outside building drainage systems including ventilation.
- Rain water discharge & harvesting for residential and commercial buildings/complexes.
- Industrial buildings and public utilities.

MAJOR ADVANTAGES

- Lighter than conventional C.I. pipes but strong.
- Compatible with other drainage products.
- Easy to install with low assembly force.
- Smooth bore.
- Leak-proof joints.
- Long-term sealing performance.
- Cost-effective.
- World-Class Seals stronger than locally available seals.**
- Long life.

**Available with Trubore forsheda rings.

JOINTING METHOD

Elastomeric Sealing Ring or Solvent Joint.

PIPE DIMENSIONS FOR SWR SYSTEMS

Pipe Size (mm)	Nominal Outside Diameter (mm)	Mean Outside Diameter (mm)		Wall Thickness (mm)			
				Type 'A'		Type 'B'	
		Min	Max	Min	Max	Min	Max
40	40.0	40.00	40.30	1.80	2.20	3.20	3.80
50	50.0	50.00	50.30	1.80	2.20	3.20	3.80
63	63.0	63.00	63.30	1.80	2.20	3.20	3.80
75	75.0	75.00	75.30	1.80	2.20	3.20	3.80
90	90.0	90.00	90.30	1.90	2.30	3.20	3.80
110	110.0	110.00	110.40	2.20	2.70	3.20	3.80
160	160.0	160.00	160.50	3.20	3.80	4.00	4.60